


Cape Town



DESALINATION – OPTION ANALYSIS

- **supply side option**
- **demand side option**
- **Environmental – reserve option**
 - **Enviro water quantum**
 - **Enviro water quality**
- **Cost analysis**



True Capex cost of water

- **Cost of dam –**
 - Enviro cost of dam – longer term effects
 - Cost of works
 - Cost of translocation – bulky infrastructure design
- **Cost of desal plant**
 - Enviro cost of plant
 - Cost of plant
 - less than dam
 - Easily upgradable
 - Cost of translocation –
 - Less pumping – less energy demand
 - closer to demand
 - Smaller pipes from dam



True Capex cost of water

- **Cost analysis**
 - **Enviro capex of abstraction**
 - **Enviro capex of discharge**
 - **Capex cost of - plant
- translocation**



Opex cost of water

- Dams further from point of demand
- Desal plants closer to point of demand
- Less pumping costs
- Less large piping costs
- Less water loss
- Desal plant operated when needed
- Operated 24/7/365 if need be
- Favourable replacement cost
- Favourable upgrading costs



Enviro cost of abstraction

- Less water abstracted from rivers – improved reserve
- Abstracting water from impacted resource - exacerbating resource quality and quantity
- Raw water exchange for recycled water or blended water for agric or industry
- more raw water for primary use such as domestic - human consumption
- More water for equity – those not having water as yet



Enviro cost of discharge

- less water discharged into rivers in coastal areas – better reserve quality of rivers – better estuaries – river and groundwater health for recreation and tourism.
- Coastal areas and inland areas
- Curtailing low quality discharge to resource



Desal Supply side option

Groundwater

- brackish/ saline waters in use at Bitterfontein on West Coast
- Viable option limited to availability of groundwater
- Near point of demand
- Can be used conjunctively
 - Increasing water security
 - Reducing risk of restrictions
 - Drought management option
 - Emergency supply
 - Minimal evaporation – excess water stored for later use
 - Artificial recharge of brackish groundwater with less saline effluent – to be extracted again for desal – closed loop



Desal Supply side option (Cont)

- Cost of water produced is also directly depended on the recovery rate. For sea water recovery is around 50%. Rest go to brine resulting in water double seawater quality!).
- For brackish groundwater such as Bitterfontein, recovery can be around 75%. For treated wastewater to make it almost potable - recovery can be up to 90%.



Supply side option – sea water

- **In 2006, the cost of water from the desalination plant in Perth, Western Australia was approximately R5/m³.**
- **The desalination plant planned for the Australian Gold Coast has an estimated cost of approx R9/m³.**



Supply side option – sea water

- A recent WRC Report (WRC Report TT 266/06 dated July 2006) calculated the unit production cost of desalination on the Cape West Coast at R7/m³.
- A figure of R6/m³ was used in the Recon Strategy for Cape Town as the approximate cost of desalination.



Desal for recycling

- Desal for recycling –up to 90% returns
- Can augment raw water supplies for
 - agric
 - Industry
- Improve river reserve
- Improve water security especially for coastal areas
- Improve growth and development prospects



Desal option

Supply side management

Recycling

- **Most readily available**
- **Cheapest water**
- **Highest assurance of supply**
- **Water with invested costs of treatment**
- **Water with invested costs of translocation**
- **Highest assurance of quality**
- **Desalination is additional cost realising maximum returns of 80/20**



Desal option

Demand side management

- **Reducing water use by reuse of fresh water containing salts – sewage effluents**
 - Industrial effluent – desalinate for production water in exchange for municipal potable water
 - Water savings on supply side as well as savings on waste water generation
 - Less environmental costs



Desal option

Demand side management

- **Desal for recycling replaces parallel supply to serial supply options**
 - **Doubling or tripling savings on quantum of supply: eg parallel supply to**
 - water to domestic
 - Water to agric
 - Water to industry
 - **serialising supply of water for domestic – treated for supply to agric – further treated for supply to industry**



Desal option

Demand side management

- Irrigation – desalinate at sewage plants for crop production as appropriate
- Supply to agric eg Western Cape – WUA utilising treated effluent for fruit trees – health precautions
- Coastal cities to utilise recycled effluent or blended with raw water rather than raw water from resource – guaranteed better quality and assurance of supply
- Higher water security
- Better food security



Spatial Desal potential mapping

- **Desal potential map for SA based on spatial offsets:**
 - **Environmental cost of water**
 - **water quality requirements**
 - **value add to water**
 - **sole source of water**
 - **food production**
 - **Industrial**
 - **etc**



Desal - mining

- Mine water – high enviro costs – desal to low enviro costs
- This desal water then utilised for domestic or industrial use
- This is total cost benefit of desal and not just cost of treatment of desal
- Total cost being
 - Enviro cost
 - Translocation cost
 - capex
 - Opex



Desal as contingency supply

- Drought management option
- Ready supply
- No lead times on start up
- plug and play option
- Portable and flexible on size of turnkey project



Desalination as climate change risk management option

- **In CC induced water stress – immediate start up option**
- **Back up option**
- **Risk management for growth and development**
- **Disaster management option**
- **Influx/outflux option**



Scenario 1


Scenario 2

Scenario 3

**Illustrates importance of
WC/WDM in timeously
meeting future water
requirements**



SCENARIO	DESCRIPTION
Scenario1	No WC/WDM. All supply interventions can be implemented
	Objective: To determine the impact of not implementing WC/WDM




Intervention	Date Study Required	Study Level Required
“fast tracked” TMG	2007	Feasibility
Newlands Aquifer	2007	Pre feasibility
Cape Flats Aquifer	2007	Feasibility

KEY FINDINGS

- Supply Intervention required by 2011 (after Berg Water Project)
- Due to long lead times earliest supply intervention could only be implemented by 2014
- To achieve this date the TMG scheme would have to be “fast tracked”
- Shortfall in supply for between 2011 and 2014


SCENARIO	DESCRIPTION
Scenario 2	CCT WC/WDM strategy & prog. implemented. All supply interventions can be implemented.
	Objective: To determine the impact of implementing the CCT's WC/WDM strategy



KEY FINDINGS	Intervention	Date Study Required	Study Level Required
	Newlands Aquifer	2007	Pre feasibility
	Upper Wit River Diversion	2007	Feasibility
	Cape Flats Aquifer	2007	Feasibility
	DWAF: West Coast Aquifers	2008	Pre feasibility

- Supply intervention required by 2013 (after Berg Water Project)
- Implementation of CCT's WDM strategy and programme allows supply interventions to be implemented without “fast tracking” or reducing implementation lead times.

SCENARIO	DESCRIPTION
Scenario 3	CCT WC/WDM strategy and programme implemented as well as additional longer term WC/WDM interventions. All supply interventions can be implemented
	Objective: To determine the impact of implementing all the WC/WDM interventions



Intervention	Date Study Required	Study Level Required
(Longer term WC/WDM)	2007	Feasibility
Voëlvlei Phase 1	2007	Feasibility
Mitchells Pass Diversion	2007	Pre feasibility
Newlands Aquifer	2009	Pre feasibility
Upper Wit River Diversion	2010	Feasibility

KEY FINDINGS

- Implementation of CCT's WDM Strategy and Programme, as well as longer term WC/WDM initiatives allows the next supply intervention to be delayed until 2017 with no restriction on implementation lead time
- Comprehensive WC/WDM (100% successful implementation) can effect a saving of approx 100 million m³ of water per annum by 2017
- 50% successful WC/WDM will delay next intervention till approx 2014
- Low Water Requirement curve and 100% successful WC/WDM will delay supply intervention till 2029
- No restriction on implementation lead times


Scenario 5

Scenario 6

**Illustrates impact of
effluent re-use and
desalination
interventions in lieu of
surface water**



SCENARIO	DESCRIPTION
Scenario 5 (a&b)	CCT WC/WDM strategy and programme implemented. Only effluent re-use interventions can be implemented.
	Objective: To determine how effluent re-use interventions could meet future demand requirements




Intervention	Date Study Required	Study Level Required
Re-use irrigation/industrial	2007	Feasibility
Dual Reticulation	2007	Feasibility
Commercial Irrigation exchange	2007	Feasibility
Treated effluent re-use to potable standards	2007	Feasibility Study
Treated effluent re-use to potable standards (reduced implementation time)	2009	Feasibility Study

KEY FINDINGS

- Treated effluent re-use schemes could be implemented to meet the increasing water demand until 2018. Thereafter there would be a potential shortfall in supply for one year prior to a treated effluent re-use intervention to potable standards being commissioned.
- In order to implement a treated effluent re-use scheme to potable standards by 2018, one would have to reduce the implementation lead times.
- Effluent re-use needs a comprehensive study to conceptualise schemes and determine full potential

SCENARIO	DESCRIPTION
Scenario 6	CCT WC/WDM strategy and programme implemented. Only desalination implemented.
	Objective: To determine how desalination interventions could meet future demand requirements



KEY FINDINGS

- Shortfall in supply from 2013 to 2016, prior to a desalination plant being commissioned. Implementation lead time would have to be reduced to implement a desalination plant by 2016
- Effluent re-use to potable standards more cost effective but has potential social impacts
- Based on the implementation timeframes of the Perth desalination plant, it may be possible to “fast track” implementation of a desalination plant by 2013


Scenario 8

Scenario 9

**Illustrates impact of
implementing ecological
Reserve as well as
potential impact of
climate change**




SCENARIO	DESCRIPTION
Scenario 8	CCT WC/WDM strategy and programme implemented. Thereafter selection based on URV (Scenario 7) with the ecological Reserve being phased in for existing water resources
	Objective: To determine how the implementation of the ecological Reserve will impact on the selection of interventions



KEY FINDINGS

- The yield of the existing water resources decreased by approx. 46 million m³.
- A mix of supply and demand interventions are available for selection in order to offset the anticipated shortfall in supply in 2103 and beyond.
- No restriction on implementation lead times
- Net present value of this option is R 4 472 million. The cost of implementing additional interventions in order to offset the anticipated decrease in system yield is approximately R 637 million in today's terms.

SCENARIO	DESCRIPTION
Scenario 9	CCT WC/WDM strategy and programme implemented. Thereafter selection based on URV (Scenario 7) with the potential for climate change being factored in
	Objective: To determine how climate change could impact on the selection of interventions



Intervention	Date Study Required	Study Level Required
(Longer term WC/WDM)	2007	Feasibility
Voëlvlei Phase 1	2007	Feasibility
Mitchells Pass Diversion*	2007	Pre feasibility
Upper Wit River Diversion	2008	Feasibility
Newlands Aquifer	2007	Pre feasibility
Cape Flats Aquifer	2009	Feasibility
Re-use irrigation/industrial	2008	Feasibility

KEY FINDINGS

- The yield from the existing water resources and future water resources was assumed to be decreased by approx. 107 million m³.
- A mix of supply and demand interventions are available for selection in order to offset the anticipated shortfall in supply in 2103 and beyond.
- No restriction on implementation lead times
- Net present value of this option is R 6 571 million. The cost of implementing additional interventions in order to offset the anticipated decrease in system yield is approximately R 2 736 million in today's terms.

INTERVENTION	REQUIRED STUDY START DATE FOR SCENARIOS											
	1	2	3	4	5(a)&(b)	6	7	8	9	10(a)	10(b)	11
CCT WC/WDM strategy and programme		2007	2007	2007	2007	2007	2007	2007	2007	2007	2007	2007
Long Term WC/WDM interventions			2007				2007	2007	2007			2007
Voëlvlei Phase 1			2007				2007	2007	2007	2007	2007	2007
Mitchells Pass Diversion			2007				2007	2007	2007	2007	2007	2007
Newlands Aquifer	2007	2007	2009	2007			2007	2008	2007			
Cape Flats Aquifer	2007	2007		2007					2009			
DWAF West Coast Aquifers		2008		2007								
"fast tracked" TMG	2007			2009						2008	2007	
Upper Wit River Diversion		2007	2010				2007	2007	2008			
Raising Steenbras Lower										2009	2007	
Lourens River Diversion											2007	
Upper Molenaars											2007	
Re-use irrigation/industrial					2007			2009	2008	2007	2007	
Dual Reticulation					2007							
Commercial Irrigation Exchange					2007							
Treated Effluent to Potable Standards					2007						2007	
Desalination						2007						

Notes:

- 1) Only study start dates between 2007 and 2009 are shown
- 2) Voëlvlei Phase 1 and Mitchells Pass are mutually exclusive schemes

	Indicates Pre feasibility level study required
	Indicates Feasibility level study required
Date	Indicates a "fast tracked" or reduced implementation time

Summary of Study Start Dates



Conclusion

1. Desal is definitely a serious option for water security

- Coastal town water regimen/ conjunctive use of fresh, groundwater and sea waters –stormwater may also be considered.

2. Desal for unlocking other sources of water - brackish alternate sources such as brackish waters inland and coastal

3. Desal for improving Resource Quality objectives



Conclusion

4. Desal for recycling of effluent should begin sooner than later

- Equity
- Reserve
- Food
- Jobs

5. Desal for extending life of existing infrastructure

- Hydraulic load
- Type of infrastructure needs

6. unlock water for: Growth and development



The end

